Positive Drive: Chain & Sprockets STRAIGHT RUNNING BELT Friction Drive : Rollers TURN & SPIRAL BELT Positive Drive : Chain & Sprockets A TOTAL BELT WIDTH - Including Washer / Edge B SPIRAL PITCH ROD PITCHES: D ROD PITCH E ROD WIRE DIA (Breakline) Rod Finish: Note: Count "spaces" in width Mushroom Edge (always odd number) C1 FLAT WIRE THICKNESS C2 FLAT WIRE HEIGHT HONEY COMB DETAIL

14/		BFI	TIN	•
w	IK-	K-I	IIIN	

BELT TYPE

STRAIGHT RUNNING BELT

NOTE: PITCH MEASUREMENT IS CENTRE TO CENTRE I MEASUREMENTS ARE ALL IN 'mm"

TOTAL BELT LENGTH:			
A - TOTAL BELT WIDTH (NB incl washer / edge) :			
B - SPIRAL PITCH :			
C1 - FLAT WIRE THICKNESS :			
C2 - FLAT WIRE HEIGHT:			
D - ROD PITCH			
E - ROD WIRE DIA.			
MATERIAL:			
SPACES IN WIDTH:			
ROD FINISH:			
CLINCHED EDGE: OR			
MUSHROOM EDGE:			

12.7mm	
15.875mm	
19.05mm	
25.4mm	
27.43mm	
28mm	
30mm	
30.5mm	
31.75mm	
38.1mm	

DRAWING: Honeycomb Belt - Flat Wire Belt

Customer :	
Contact Person :	
Contact Number:	
Email :	

APPROVED FOR MANUFACTURE SIGNATURE:

www.tegman.co.za

sales@tegman.co.za

031 563 4252 / 072 299 4947